

## Indexes for the evaluation of a Solar Tracker\*

### Índices para la evaluación de un seguidor solar

Carlos R. Batista-Rodríguez\*\*  
*Universidad Antonio Nariño, Colombia*

Rosa I. Urquiza-Salgado\*\*\*

Elio R. Hidalgo-Batista\*\*\*\*  
*Universidad de Holguín, Cuba*

---

\* This work was supported by Antonio Nariño University, within the remit of an internally financed research project, code 201 6209.

\*\* Ph. D. in Technical Sciences, Mechanical Engineer. Professor in the Mechanical Engineering program in Universidad Antonio Nariño, Tunja, Colombia. [carlos.batista@uan.edu.co](mailto:carlos.batista@uan.edu.co)

\*\*\* Ph. D. in Mathematical Sciences, Bachelor in Mathematics and Physics. Professor in the Bachelors of Mathematics program and Director of Applied Mathematics and Informatics for Administration Master Program in University of Holguín, Cuba. [rurquiza@uho.edu.cu](mailto:rurquiza@uho.edu.cu)

\*\*\*\* M.S. in Agricultural Machinery, Mechanical Engineer. Assistant Professor in the Mechanical Engineering program in University of Holguín, Cuba. He will present his Ph. D. dissertation in Technical Sciences in December 2017. [elio@uho.edu.cu](mailto:elio@uho.edu.cu)

## Abstract

The usage of solar trackers in solar energy technologies represents an alternative to increase the capture of solar radiation. However, the costs involved make it a prohibitive technology, having indexes and procedures that allow for its evaluation and determination of the viability of its use is of vital importance at the time of deciding its implementation and so to form the objective of this study. In the investigation carried out, the indexes of average gain, comparative efficiency and profitability are introduced and a procedure for the evaluation is developed, as a contribution to the decision-making process as to whether or not to use a solar tracker. It is confirmed that the use of trackers is completely viable when used with higher power technologies. Furthermore, it is shown that theoretically, the average gain index is higher than the values currently registered in scientific literature. Such factors support the possibility of designing and developing solar trackers with a higher gain, lower production costs and lower consumption indexes, as a way for their mass use in low power photovoltaic generators.

**Keywords:** efficiency, evaluation technologies, indexes gain, profitability, selection, solar tracker.

## Resumen

El uso de los seguidores solares como tecnología de aprovechamiento de energía solar representa una alternativa para incrementar la captación de radiación solar. Sin embargo, sus costos lo convierten en una tecnología prohibitiva, por lo que disponer de índices y procedimientos que permitan su evaluación para determinar la viabilidad de uso es una herramienta de extrema importancia a la hora de decidir sobre su utilización y constituye el objetivo de este trabajo. Con la investigación realizada se introducen los índices de ganancia media, eficiencia comparativa y de utilidad y se desarrolla un procedimiento de evaluación, como contribución a la toma de decisiones sobre el uso o no de un seguidor solar. Se corrobora que su uso es totalmente viable mientras mayor es la potencia de las tecnologías en las cuales se utiliza. Además, se muestra que teóricamente el índice medio de ganancia es mayor que los valores registrados actualmente en la literatura científica. Tales elementos apoyan la posibilidad de diseñar y desarrollar seguidores solares con mayor ganancia, menores costos de fabricación y menores índices de consumo, como vía para su utilización masiva en generadores fotovoltaicos de baja potencia.

**Palabras claves:** eficiencia, evaluación tecnologías, índices ganancia, seguidor solar, selección, utilidad.

Fecha de recepción: 28 de enero de 2017  
Fecha de aceptación: 22 de septiembre de 2017

## I. INTRODUCTION

Currently, in many developing countries, there still exist areas where electrical energy is not available [1], the fundamental cause being a disperse, low-income, rural population in regions where access is difficult. Because of this, taking advantage of low cost and highly efficient photovoltaic solar energy [2], [3] represents one possible solution. The use of solar trackers represents an alternative to improve efficiency during the exploitation of solar energy [4], [5]. This mechanism ensures that the light with maximum intensity will be falling on the solar panel throughout the day. In other words, it is an effort to increase the efficiency of power generation through the solar module.

In the international market, a diverse selection of solar trackers exists, however, end-users do not have a guide or method that allows them to decide whether using one is viable in specific operating conditions. Additionally, comparative indexes are not available to evaluate whether the gain indicated by the producer and paid for corresponds with the operating results of the solar tracker.

An analysis of the techno-economic efficiency (kWh/\$) of solar technologies such as photovoltaic generator and solar heater, allows us to conclude that they are not financially viable on the global market with respect to other traditional technologies that are available to produce heat and electricity. To take into account the studies carried out by [6], "the cost factor is more important than the efficiency". Considering this information and the need that exists to design and develop a hybrid micro technology in order to generate electric and caloric energy at a low cost to rural zones without supplied electricity, it becomes necessary to research solar trackers including determining how much the efficiency of solar technologies could be improved.

Upon numerous reviews of solar trackers, it can be concluded that indexes or methodology to evaluate its usage do not exist. There are, however, some comparative analyses of solar tracker usage, according to studies carried out by authors [7]-[21]. Taking into account that, from a scientific perspective, no indexes have been designed to evaluate the viability of the use of a solar

tracker for a specific solar energy facility, providing objective elements to make the decision to select or not that technology, the aim of this work was to design a group of techno-economic indexes and to propose a procedure based on these indicators which allow for the user to be guided in order to properly select and/or evaluate a solar tracker and, consequently, to determine whether its use is viable. The hypothesis is: the existence of a methodology based on techno-economic indexes would permit evaluating the solar trackers, and to determine whether its use is viable.

It is known that the nominal power ( $P_n$ ) of a photovoltaic generator is calculated during operation in a fixed horizontal position ( $\beta = 0$ ), with a solar irradiance coefficient  $I_o = 1\text{kW}/\text{m}^2$ , a determined spectrum of radiation falling upon it and cells that continue working at a temperature of  $25^\circ\text{C}$  [22]-[25]. However, by using solar trackers (mobile supports) their operational power could be increased by between 25-55% [26] - [30]. How can it be determined whether the use of solar trackers is economically viable?

It is known that the average density of the solar radiation that arrives at the highest part of the atmosphere is  $1366\text{ W}/\text{m}^2$  [23], [31], known as the solar constant. Notwithstanding, due to the phenomena of reflection, absorption and atmospheric transmittance along with the infrequent occurrence of clear sky conditions, the maximum irradiance value observed at the surface of the earth is  $I_o = 1\text{kW}/\text{m}^2$ .

When assessing the energetic potential of a region, the parameter which needs to be calculated is the irradiance: the quantity of energy irradiated ( $H$ ) in a period of time calculated by the formula  $H = \int_{t_1}^{t_2} I(t)dt$ , referred to as solar irradiation between two moments of time [24]. This formula can be used to make daily, monthly or yearly calculations where  $I(t)$  is the real function of irradiance, established for different moments of time.

In this study, it is assumed that the gain index ( $I_c$ ) of a solar tracker is the relation between the quantity of energy generated during a period of time by a piece of technology exploiting solar energy installed on a mobile support, with respect to the quantity of energy that is possible to generate in the same period of time by the same technology, were it to be installed on a fixed support.

To carry out the calculation, it is necessary first to determine the maximum quantity of energy that it is possible to generate using technology mounted on an ideal mobile support, which at every moment of time modifies the Polar angle ( $\beta$ ) and Azimuth angle ( $\gamma$ ) values of the surface receiving solar rays and ensures that the Incidence angle ( $\theta$ ) on the receiving surface is zero degrees, for which its cosine will always be the unit and it will be calculated using the formula (1):

$$E_{GSS} = H_{SS} = \int_{t_s}^{t_p} I(t) dt = I_0 \cos \theta \int_{t_s}^{t_p} dt \quad (1)$$

In (1) it is understood that:

$E_{GSS}$  - Quantity of energy generated by a piece of solar technology mounted on a mobile support or a solar tracker;

$t_s$  - Time of sunrise;

$t_p$  - Time of sunset.

Note that in the given situation,  $E_{GSS}$  coincides with the maximum possible irradiated energy.

Given that  $\cos(\theta) = 1$ , the formula (1) transforms into (2):

$$E_{GSS} = I_0 (t_p - t_s) \quad (2)$$

However, for a case in which the support is fixed, as the hours and days go by, the angle  $\theta$  varies [32], because of which the calculation of its value at a given moment may be realized by using the formula (3):

$$\begin{aligned} \cos \theta = & \sin \delta (\sin \varnothing \cos \beta - \cos \varnothing \sin \beta \cos \gamma) + \\ & + \cos \delta (\cos \varnothing \cos \beta \cos \omega + \sin \varnothing \sin \beta \cos \gamma \cos \omega + \sin \beta \sin \gamma \sin \omega) \end{aligned} \quad (3)$$

whence,

$\delta$  - Solar declination;

$\omega$  - Daylight hours' angle;

$\varphi$  - Latitude;

$i, j, k$  - Unit vectors;

$\beta$  - Polar angle;

$\gamma$  - Azimuth angle.

The  $\cos(\theta)$  is obtained as a vector product of solar vector ( $\vec{S}$ ), given in equation (4), by the normal vector ( $\vec{N}$ ) to a surface with an arbitrary orientation on the earth, which appears in equation (5)

$$\vec{S} = i(\cos \delta \cos \omega \sin \varphi - \sin \delta \cos \varphi) + j(\cos \delta \cos \omega) + k(\cos \delta \cos \omega \cos \varphi + \sin \delta \sin \varphi) \quad (4)$$

$$\vec{N} = i(\sin \beta \cos \gamma) + j(\sin \beta \sin \gamma) + k \cos \beta \quad (5)$$

According to studies carried out by various authors [23], [33] and calculations included in the present study (see Table 1), the best solar ray capture variant would be for a surface with an inclination angle of  $\beta = \varphi$  fixed throughout the year (that is, equal to the angle given by the latitude of the place) and focused towards the south, because of which the Azimuth angle  $\gamma = 0$ . If said values are substituted into formula (3), an incidence angle of solar rays on the Surface would be given by:

$$\cos \theta = \cos \delta \cos \omega \quad (6)$$

If formula (6) is integrated for the irradiance of  $I_0$  in a period of 24 hours, the maximum possible irradiation of the surface is obtained, which would be considered as the maximum quantity of energy that a piece of solar technology mounted on a fixed support could generate with the angles  $\beta = \varphi$  y  $\gamma = 0$ , formula (7):

$$E_{GF} = H_{(\beta=\varphi, \gamma=0)} = \frac{24}{2\pi} \int_{-\frac{\pi}{2}}^{\frac{\pi}{2}} I_0 \cos \theta d\theta = \frac{12}{\pi} I_0 \cos \delta \int_{-\omega_s}^{\omega_s} \cos \omega d\omega \quad (7)$$

Definitively, the highest quantity of energy that can be generated by a piece of solar technology on a fixed installation ( $E_{GF}$ ) is given by formula (8):

$$E_{GF} = \frac{24}{\pi} I_0 \cos(\delta) \sin(\omega_s) \quad (8)$$

For the calculation of the gain index for any angle  $\beta$  and any angle  $\gamma$ , formula (3) is integrated for the irradiance of  $I_0$  in a period of 24 hours and formula (9) is obtained:

$$H_{(\beta,\gamma)} = \frac{24}{\pi} \sin \omega_s (\cos \varnothing \cos \beta \cos \delta + \sin \varnothing \sin \beta \cos \gamma \cos \delta) + \frac{24}{\pi} \omega_s (\sin \varnothing \cos \beta \sin \delta - \cos \varnothing \sin \beta \cos \gamma \sin \delta) . \quad (9)$$

## II. METHODOLOGY

The process for the calculation of the indexes will allow for the adequate selection and evaluation of a solar tracker, to determine the viability of its use.

### Calculation methodology

From the equations available in the introduction of this study and their respective relations, this study proposes the calculation of the following indexes:

1. Index of theoretical gain ( $I_G$ ) of the solar tracker: obtained by dividing the maximum possible generation with a mobile support, formula (2), by the maximum generation possible with a fixed support, given by (8):

$$I_G = \frac{E_{GSS}}{E_{GF}} = \frac{\frac{24}{\pi} I_0 (t_p - t_s)}{\frac{24}{\pi} I_0 \cos \delta \sin \omega_s} = \frac{(t_p - t_s) \pi}{24 \cos \delta \sin \omega_s} \quad (10)$$

Note that the theoretical gain index over the course of a year can take different values: a maximum value when the Earth is in summer solstice (20/21 June) where  $\delta = 23,44$  degrees and  $I_G = 1,76$ ; a minimum value when

the Earth is at the spring equinox (20/21 March), when  $\delta = 0$  and  $I_G = 1,57$  for the specific geographical conditions, see Table 2.

2. Solar tracking consumption index ( $I_{CS}$ ): is defined as the total consumption of electric energy of its motors, in a unit of time, needed to be able to track the solar rays.
3. Comparative gain index ( $I_{CG}$ ): the ratio between the solar tracker's gain index and the maximum average gain ( $I_{GM}$ ) that can be obtained with a solar tracker over the course of a year. It is calculated as the mean value for the four seasons of the year, taking specifically the values corresponding to the summer and winter solstice and spring and autumn equinoxes.

$$I_{CG} = \frac{I_{GS}}{I_{GM}} \quad (11)$$

whence,

$I_{GS}$  - Index of solar tracker gain by manufacturer.

4. The utility of solar technology without solar tracker (with fixed support)  $U_{TF}$  is calculated by the expression:

$$U_{TF} = P_{op} \Delta t T_f - C_{TF} \quad (12)$$

whence,

$C_{TF}$  - Cost of the acquisition of the technology of electrical energy production from solar energy, mounted on a fixed support;

$T_f$  - Electricity consumption rate in the locality where the analysis will be carried out;

$P_{op}$  - Operating power of the solar technology taking into account the factor of solar peak hours;

$\Delta t$  - Time interval for which the utility analysis is performed. It can be a day, a month, a year, etc.



5. The utility of solar technology with solar tracker (with mobile support)  $U_{TM}$ : is calculated by the expression:

$$U_{TM} = (P_{op} - I_{CS}) I_{GS} \Delta t T_f - (C_{TF} + C_S) \quad (13)$$

So:

$C_S$  - Acquisition cost of solar tracker.

6. Index of utility: relation between the utility with mobile support and the utility with fixed support:

$$I_U = \frac{U_{TM}}{U_{TF}} * 100 \quad (14)$$

With the proposed indexes, the solar tracker is selected and/or evaluated by the following procedure:

1. The commercial data of the solar tracker are obtained: Cost of acquisition ( $C_S$ ), Index of profit ( $I_{GS}$ ), Index of consumption ( $I_{CS}$ ).
2. The commercial data of the electric production technology from the solar energy are obtained: Cost of acquisition ( $C_{TF}$ ), Nominal power ( $P_n$ ).
3. Data are obtained from the location where the technology will be installed: latitude, solar peak hours or solar performance index ( $I_{RS}$ ), as well as the electric consumption tariff ( $T_f$ ) of the locality.
4. The maximum average gain ( $I_{GM}$ ) and the operational power of the technology ( $P_{op}$ ) are calculated for the geographic and climatological conditions of the place where the technology will be installed.
5. The Gain Comparison Index ( $I_{CC}$ ) is calculated.
6. The utility of technology with fixed support and mobile support for a certain time interval (usually one year) is calculated.
7. The utility index is calculated.

8. The analysis is carried out and decisions are made as to whether or not the use of the solar tracker is feasible for the operating conditions of the electric energy production technology from solar energy.

### Materials used

Irradiation map of Colombia, NASA database [34], for the average solar irradiance of the city of Tunja; current rates of kWh price, in the city of Tunja [35].

### III. RESULTS AND DISCUSSION

Once the procedure was developed, it was applied to evaluate a mobile support. The data are recorded in Table 1. The data of the calculations of gain indexes are shown in Table 2, while the values of the utility index appear in Table 3.

**Table 1.** Data recorded for solar tracker evaluation

No	Registered Data	u/m	Value
1	Cost of acquisition ( $C_g$ ),	COP	735.000
2	Solar Tracker Gain Index ( $I_{GS}$ )	-	1,4
3	Index of solar tracker consumption	W/d	10
5	Electricity Consumption Rate	COP/kWh	366
6	Latitude of the city of Tunja	degrees	5,533
7	Cost of acquisition of the photovoltaic panel	COP	3.200.000
8	Rated power ( $W_p$ ) of the photovoltaic panel	W	1.000
9	Tunja Solar Performance Index		0,7

**Table 2.** Calculation of gain index

$\gamma = 0$	$\delta$												$I_{GM}$	$H_{(\beta,\gamma)m}$
	23,44			0,0			-23,44			0,0				
$\beta$	$H_{(\beta,\gamma)}$	$H_{SS}$	$I_G$	$H_{(\beta,\gamma)}$	$H_{SS}$	$I_G$	$H_{(\beta,\gamma)}$	$H_{SS}$	$I_G$	$H_{(\beta,\gamma)}$	$H_{SS}$	$I_G$		
0	7,44	12,32	1,66	7,60	11,99	1,58	6,52	11,68	1,79	7,60	12,00	1,58	1,65	7,29
1	7,37	12,32	1,67	7,62	11,99	1,57	6,61	11,68	1,77	7,62	12,00	1,58	1,65	7,30
2	7,29	12,32	1,69	7,62	11,99	1,57	6,70	11,68	1,74	7,62	12,00	1,57	1,64	7,31
3	7,21	12,32	1,71	7,63	11,99	1,57	6,79	11,68	1,72	7,63	12,00	1,57	1,64	7,32
4	7,13	12,32	1,73	7,64	11,99	1,57	6,88	11,68	1,70	7,64	12,00	1,57	1,64	7,32
5	7,05	12,32	1,75	7,64	11,99	1,57	6,96	11,68	1,68	7,64	12,00	1,57	1,64	7,32
5,533	7,00	12,32	1,76	7,64	11,99	1,57	7,00	11,68	1,67	7,64	12,00	1,57	1,64	7,32
6	6,96	12,32	1,77	7,64	11,99	1,57	7,04	11,68	1,66	7,64	12,00	1,57	1,64	7,32
7	6,88	12,32	1,79	7,64	11,99	1,57	7,12	11,68	1,64	7,64	12,00	1,57	1,64	7,32
8	6,79	12,32	1,82	7,63	11,99	1,57	7,20	11,68	1,62	7,63	12,00	1,57	1,65	7,31
9	6,69	12,32	1,84	7,63	11,99	1,57	7,27	11,68	1,61	7,63	12,00	1,57	1,65	7,30
10	6,60	12,32	1,87	7,62	11,99	1,57	7,34	11,68	1,59	7,62	12,00	1,58	1,65	7,29
15	6,10	12,32	2,02	7,54	11,99	1,59	7,67	11,68	1,52	7,54	12,00	1,59	1,68	7,21
20	5,56	12,32	2,22	7,40	11,99	1,62	7,94	11,68	1,47	7,40	12,00	1,62	1,73	7,07
25	4,97	12,32	2,48	7,20	11,99	1,66	8,15	11,68	1,43	7,20	12,00	1,67	1,81	6,88

On Table 2, it can be observed that the average gain index ( $I_{GM}$ ) is very stable for inclination angles between 0 and 10 degrees, as well as the production of electric energy from fixed-beam solar technologies ( $H_{(\beta,\gamma)}$ ). However, by increasing the inclination angle of the fixed support, the generation of fixed technology decreases its production and increases the rate of gain.

**Table 3.** Calculation of the utility index

Years	Days	$U_{TF}$	$U_{TM}$	$I_U$
	1	-\$3.196.950,70	-\$3.930.736,10	-1,23
	30	-\$3.108.520,91	-\$3.807.083,00	-1,22
1	365	-\$2.087.004,46	-\$2.378.676,50	-1,14
2	730	-\$974.008,91	-\$822.353,00	0,84
3	1095	\$138.986,63	\$733.970,50	5,28
4	1460	\$1.251.982,17	\$2.290.294,00	1,83
5	1825	\$2.364.977,71	\$3.846.617,50	1,63
6	2190	\$3.477.973,26	\$5.402.941,00	1,55
7	2555	\$4.590.968,80	\$6.959.264,50	1,52
8	2920	\$5.703.964,34	\$8.515.588,00	1,49
9	3285	\$6.816.959,89	\$10.071.911,50	1,48
10	3650	\$7.929.955,43	\$11.628.235,00	1,47

Table 3 shows that the usefulness of  $U_{TM}$  mobile technologies for short periods (less than one year) is lower than the usefulness of fixed technologies due to their investment costs. However, as of the second year of operation, the profits of the mobile technologies are higher than the fixed ones and it is reflected in a positive utility index  $I_U = 0,84$ , with a rapid tendency to grow. It becomes more stable as time goes on, with a slight tendency to decrease, due to the consumption of the engines for the mobile technologies. The factors that would increase the utility index would be a higher profit rate (from 1,4 to 1,64), a decrease in solar tracker investment costs, as well as engine consumption. It should be noted that the utility index has a faster growth rate for technologies with higher nominal powers.

#### IV. CONCLUSIONS

This investigation proposed a group of techno-economic indexes (average gain, comparative efficiency and profitability) as a first stage in the contribution to the decision-making process on the suitability, or lack thereof, to use a solar tracker. With the designed indicators, a procedure that permits to evaluate the viability of the use of a solar tracker for a specific solar energy

facility was developed, providing objective elements to make the decision; that is to select or not to select that technology. The use of solar trackers for technologies of greater power favors its utility index.

With the calculations made on the gain index, it can be observed that the average value obtained for fixed installations with an inclination angle equal to the latitude of the site is superior to the values registered in the literature, which shows the possibility of designing and developing trackers with higher solar gain, lowering manufacturing costs and lowering consumption rates as a way of using them in low-power photovoltaic generators.

## REFERENCES

- [1] Ducas and A. Ballesteros, "Clean energy access in developing countries: perspectives on policy and regulation", World Resources Inst. Issue Brief, Washington, DC, Tech. Rep. 978-1-56973-865-8, Jun. 2015.
- [2] S. Lakeou et al., "Design of a Low-cost Digital Controller for a Solar Tracking Photo-Voltaic (PV) Module and Wind Turbine Combination System", in Proceedings of the 21st European Photovoltaic Solar Energy Conference, 4-8, Dresden, Germany, 2006.
- [3] V. Poulek, and M. Libra, "New Solar Tracker". *Solar Energy Materials and Solar Cells*, vol. 51, pp. 113–120, August, 1998.
- [4] A.J. Reyes, "Diseño de un seguidor solar para cubierta a dos ejes y modular", M.S. tesis, Departamento de Física Aplicada, Universidad de Córdoba, Córdoba, Colombia, 2013.
- [5] H. D. Johnson, "Solar Tracker B- Term Report", M.S. thesis, Worcester Polytechnic Inst., Worcester, Massachusetts, USA, 2012.
- [6] A.E. Ávila, J. M. Mendoza y J. F. Beltrán, "Energy assessment of a double cover flat-plate solar collector", *Ingeniería & Desarrollo*, Universidad del Norte, 27: 93-112, 2010.
- [7] M. Mehrdash *et al.*, "Performance Evaluation of Sun Tracking Photovoltaic Systems in Canada", in Proceedings of the 20th Annual International Conference on Mechanical Engineering-ISME2012. School of Mechanical Eng., Shiraz University, Shiraz, Iran, Performance pp. 18–21, 2012.
- [8] S. Kusekar, "Tracking Of Solar Panel By Hydraulic System". *Int. J. of Informative & Futuristic Research (IJIFR)*, vol. 2, no. 8, pp. 2856–2881, 2015.
- [9] IEC-62108, "Specifications of solar trackers used for photovoltaic systems", International Electrotechnical Commission, pp. 3–26, 2007.

- [10] J. Ganesh *et al.*, "Design and Development of a Sun Tracking mechanism using the Direct SMA actuation", Department of Mechanical Engineering, Texas A&M University, College Station, TX, USA. 2004.
- [11] S. Odeh and H. Abu-Mulaweh, "Design and development of an educational solar tracking parabolic trough collector system", *Global J. of Eng. Education*, vol. 15, no. 1, pp. 21-27, 2013.
- [12] M. Clifford and D. Eastwood, "Design of a novel passive solar tracker", *Solar Energy*, vol. 77, pp. 269-280, 2004.
- [13] A. Al-Mohamad, "Efficiency improvements of photo-voltaic panels using a Sun-tracking system", *Applied Energy*, vol. 79, pp. 345-354, 2004.
- [14] A.J. Huang, W. L. Ding and Y. C. Huang, "Long-term field test of solar PV power generation using one-axis 3-position sun tracker", *Solar Energy*, vol. 85, no. 9, pp. 1935-1944, 2011.
- [15] S. Absallah and O. Bradan, "Sun tracking system for productivity enhancement of solar still", *Science Direct Desalination*, vol. 220, pp. 669-676, 2008.
- [16] A. Garg *et al.*, "Solar Tracking : An Efficient Method Of Improving Solar Plant Efficiency", *Int. J. of Electrical and Electronics Engineers*, vol. 7, no. 1, pp. 199-203, 2015.
- [17] S. Kivrak, M. Gunduzalp and F. Dincer, "Theoretical and experimental performance investigation of a two- axis solar tracker under the climatic condition of Denizli, Turkey", *Przeegląd Elektrotechniczny (Electrical Review)*, no. 2, pp. 332-336, 2012.
- [18] T. Tudorache, C. Oancea and L. Kreindler, "Performance Evaluation Of A Solar Tracking PV Panel", *U.P.B. Sci. Bull., Series C*, vol. 74, pp. 3-10, 2012.
- [19] R. Dhanabal *et al.*, "Comparison of Efficiencies of Solar Tracker systems with static panel Single- Axis Tracking System and Dual-Axis Tracking System with Fixed Mount", *Int. J. of Eng. and Technology (IJET)*, vol. 5, no. 2, pp. 1925-1933, 2013.
- [20] S. Ghosh and S. Roy, "Designing a Dual-Axis Solar Tracking System", *Int. J. Adv. Res. Electr. Electron. Instrum. Eng.*, vol. 5, no. 12, pp. 9039-9043, 2016.
- [21] P. Gupta *et al.*, "Azimuth-Altitude Dual Axis Solar Tracker", *IOSR J. Electr. Electron. Eng.*, vol. 11, no. 5, pp. 26-30 2016.
- [22] H. Magaña *et al.*, "Diseño de un Seguidor Solar para Eficientar la Captación de la Energía Solar en los Paneles Fotovoltaicos", Trabajo de grado, Programa de Ingeniería Industrial, Instituto Tecnológico Superior de Aranda, Aranda, Colombia, 2010.
- [23] J. Chen, "Tracking sunlight", in *Physic of Solar Energy*. New Jersey: JOHN WILEY & SONS, INC, 2011, ch. 4, pp. 77-104.

- [24] Orbeago y R. Arivilca, "Energía Solar Fotovoltaica. Manual técnico para instalaciones domiciliarias", Green Energy Consultoría y Servicios SRL, proyecto I+D 772, 2010.
- [25] R. E. Horn, "Dimensionamiento de un sistema FV (Parte 1)", en Memorias del XIX Simposio Peruano de Energía Solar, Puno, 2001, pp. 14-17.
- [26] A. Hsing, "Solar Panel Tracker", M.S. thesis, Elect. Eng. Dept., California Polytechnic State University, San Luis Obispo, USA, 2010.
- [27] G. A. Mendoza, "Seguidor dinámico solar para incrementar la eficiencia de placas fotovoltaicas mediante fotocélulas y servomotores controlados por un microcontrolador", Trabajo final de grado, Facultad de Ingeniería Mecánica, Universidad Politécnica de Valencia, Valencia, España, 2015.
- [28] S. Bazyari *et al.*, "A Study on the Effects of Solar Tracking Systems on the Performance of Photovoltaic Power Plants", *J. of Power and Energy Eng.*, vol. 2, pp. 718-728, 2014.
- [29] S. J. Medina, "Diseño de un Sistema Mecatrónico para el Seguimiento Solar Basado en Control Adaptativo", Trabajo de grado, Facultad de Ingeniería, Programa de Ingeniería en Mecatrónica, Universidad Militar Nueva Granada, Bogotá, Colombia, 2015.
- [30] T. Tudorache and L. Kreindler, "Design of a Solar Tracker System for PV Power Plants", *Acta Polytechnica Hungarica*, vol. 7, no. 1, pp. 23-39, 2010.
- [31] M. Caipe y A. Celis, "Diseño de una Estructura Móvil para un Panel Solar de 205 W con Dos Grados de Libertad", Trabajo de grado, Facultad de Ingeniería, Departamento de Electrónica, Pontificia Universidad Javeriana, Bogotá D.C., Colombia, 2013.
- [32] R. J. Mosquera y R. J. Betancourth, "Diseño de un Mecanismo de Cuatro Barras Esférico para la Orientación de Paneles Solares", Trabajo de grado, Facultad de Ingeniería Mecánica, Universidad Tecnológica de Pereira, Pereira, Risaralda, Colombia, 2014.
- [33] S. E. Turrillas y J. A. Garcia, "Estudio comparativo de la eficiencia energética en seguidores solares", Trabajo de grado, E.T.S. de Ingeniería Industrial, Inf. y Telecomunicación, Universidad Pública de Navarra (UPNA), Nafarroako, España, 2014.
- [34] P. Stackhouse and J. Kusterer. (2016). *NASA Surface meteorology and Solar Energy* [online] Available Tables. FTP: [https://eosweb.larc.nasa.gov/cgi-bin/sse/grid.cgi?&num=107096&lat=5.533&hgt=100&submit=presentar&veg=17&sitelev=&email=skip@larc.nasa.gov&p=grid\\_id&p=avg\\_dnr&p=sunset\\_h\\_a&step=2&lon=-73.367](https://eosweb.larc.nasa.gov/cgi-bin/sse/grid.cgi?&num=107096&lat=5.533&hgt=100&submit=presentar&veg=17&sitelev=&email=skip@larc.nasa.gov&p=grid_id&p=avg_dnr&p=sunset_h_a&step=2&lon=-73.367)
- [35] M.A. Villamarin, "Diseño de un soporte móvil para un sistema generador solar", Trabajo de grado, Facultad de Ingeniería Mecánica, Universidad Antonio Nariño, Tunja, Colombia, 2016.